



SIR-30

Rugged, High-Performance Multi-Channel GPR Data Acquisition System

The SIR-30 is the next generation high-performance multi-channel radar control unit. This system can collect up to four channels of data simultaneously with uncompromised performance.

The SIR-30 offers advanced filters and display capabilities for real-time processing including migration, surface positioning, signal floor tracking and adaptive background removal.

As the basis of a high-speed data collection system, the SIR-30 is ideal for: measuring pavement layer thickness, detection of cavities, airport runway assessment, detection of fouled/clean ballast and utility detection.

Typical Uses

- Road structure assessment
- Utility designation
- Bridge deck inspection
- Rail bed inspection



Flexible, Modular Design

- Available in a two or four channel configuration
- Operate the control unit with a laptop computer or as a standalone system
- Compatible with all GSSI antennas

Integrated System

- Ideal for vehicle-mounted applications, supports AC or DC operation
- Full internal GPS logging capability
- Multiple mounting configurations

Deliver Results

- High speed GPR data collection-capable of more than 1,375 scans/second, per channel
- Up to 500 GB data storage
- USB/ Ethernet/ Compact flash ports for system flexibility



System

Antennas	Compatible with all GSSI antennas
Number of Channels	Records data from 1 to 4 hardware channels simultaneously
Data Storage	Internal memory: 4 channel 500 GB Internal SSD 2 channel 250 GB Internal SSD GPS data logged internally
Display Modes	Linescan and O-scope. In Linescan display, 256 color bins are used to represent the amplitude and polarity of the signal
Operational Modes	External laptop, standalone with external monitor and keyboard and a remote command set

Data Acquisition

Data Format	RADAN (.dzt)																								
Scan Rate Examples	Output Data Resolution: 32-bit <table border="1"><thead><tr><th colspan="2">1-4 Channels @ 100 KHz PRF</th><th colspan="2">1-4 Channels @ 730 KHz PRF</th></tr><tr><th>Samples</th><th>Max Rate (scans/Sec)</th><th>Samples</th><th>Max Rate (scans/Sec)</th></tr></thead><tbody><tr><td>256</td><td>326</td><td>256</td><td>1375</td></tr><tr><td>512</td><td>178</td><td>512</td><td>932</td></tr><tr><td>1024</td><td>93</td><td>1024</td><td>563</td></tr><tr><td>2048</td><td>48</td><td>2048</td><td>322</td></tr></tbody></table>	1-4 Channels @ 100 KHz PRF		1-4 Channels @ 730 KHz PRF		Samples	Max Rate (scans/Sec)	Samples	Max Rate (scans/Sec)	256	326	256	1375	512	178	512	932	1024	93	1024	563	2048	48	2048	322
1-4 Channels @ 100 KHz PRF		1-4 Channels @ 730 KHz PRF																							
Samples	Max Rate (scans/Sec)	Samples	Max Rate (scans/Sec)																						
256	326	256	1375																						
512	178	512	932																						
1024	93	1024	563																						
2048	48	2048	322																						
Scan Rate Interval	User-selectable																								
Samples per Scan	256, 512, 1024, 2048																								
Operating Modes	Continuous (time) or survey wheel (distance triggered)																								
Time Range	0-16,000 nanoseconds full scale, user-selectable Gain: manual adjustment from -42 to +126 dB. Number of segments in gain curve is user-selectable from 1 to 8.																								
Standard Real-Time Filters	Infinite Impulse Response (IIR) - Low and High Pass, vertical and horizontal Finite Impulse Response (FIR) - Low and High Pass, vertical and horizontal																								
Advanced Real-Time Filters	Migration, Surface Position Tracking, Signal Floor Tracking, Adaptive Background Removal																								
External Marker	Three different inputs/codes: Antenna, Back panel, Accessory connector																								
Automatic System Setups	Storage of an unlimited number of system setup files for different survey conditions and/or antenna deployment configurations																								

Languages

English

Operating

Operating Temperature	-10°C to 40°C external (14°F to 104°F)
Power	260W max (120W typical) at 95-250VAC 50/60Hz or +10VDC to +28VDC
Transmit Rate	Up to 730 KHz (International), Up to 100 KHz (US/Canada)

Input/Output

Available Ports	Antenna inputs (2 or 4), Survey wheel, Marker, DC power input, Serial RS232 (GPS port), Sync connector, Accessory connector, HDMI video, Ethernet to PC, 4 USB ports
-----------------	--

Mechanical

Dimensions	17.7 x 13 x 5.1 in (45 x 33 x 13 cm)
Weight	18.5 lbs (8.4 kg)
Relative Humidity	<95% non-condensing
Storage Temperature	-40°C to 60°C

Antennas and accessories sold separately.
FCC, RSS-220 and CE Compliant.

